

Professional Installation Laser Projector

ZU500T-W

Stunning projection with flexible installation



- Bright 5,000 lumens and WUXGA resolution
- Four corner correction for simple stacking
- 360° and portrait mode operation
- Up to 30,000 hour light source life
- Integrated HDBaseT support
- Horizontal & vertical lens shift, keystone correction

PRO|SCENE



WUXGA

Full 3D



Experience bright 5,000 lumen WUXGA projection with the lamp-less Optoma ProScene ZU500T. Laser phosphor technology eliminates the need for lamp and filter replacements for 30,000 hours of low-cost and virtually maintenance-free operation.

Its low weight and quiet operation make it perfect for boardrooms, higher education, houses of worship and smaller entertainment venues. Horizontal and vertical lens shift, four corner correction, 360° and portrait mode operation enable flexible installations.

A variety of inputs, including HDBaseT and HDMI, enable simple connections to a wide variety of video sources. HDBaseT connectivity facilitates easy installations, enabling long cable runs of up to 328 feet for audio, video and control from a single CAT6 cable.

CONNECTIVITY (May require optional accessories)



Computers



Smart Phones



Tablets



3D Blu-ray/DVD Players



Camcorders



Apple TV®



Chromecast™

Professional Installation Laser Projector - ZU500T-W

OPTICAL/TECHNICAL SPECIFICATIONS

| | |
|---|--|
| Display Technology | Single DMD, 0.67" WUXGA DMD, DC3 DLP® Technology by Texas Instruments™ |
| Color Wheel | 4 Segment RYGB |
| Native Resolution | WUXGA (1920 x 1200) |
| Maximum Resolution | WUXGA (1920 x 1200) |
| Brightness | 5,000 ANSI lumens |
| Contrast Ratio | 300,000:1 (ExtremeBlack enabled) 1,800:1 full on/full off |
| Displayable Colors | 10 bit, 1.07 billion colors |
| Light source life* | Up to 30,000 hrs (Eco), 20,000 hrs (Bright) |
| Light source type* | Laser Phosphor |
| Projection Method | Front, rear, ceiling mount, table top |
| Keystone Correction | ±30° vertical and horizontal |
| Geometry | Four corner adjustment |
| Lens shift | Horizontal ±10%, vertical +20% |
| Uniformity | 85% |
| Offset | 100 - 120% |
| Aspect Ratio | 16:10 (native), 16:9 and 4:3 compatible |
| Throw Ratio | 1.2 - 1.92 |
| Max Projection Distance | 4 ft/1.24m - 27.1 ft /8.27m |
| Image Size | 30" - 300" |
| Projection Lens | 1.6x zoom F/2.3~3.01; f=17.63~31.36mm |
| Optical Zoom | 1.6x |
| Digital Zoom | 0.8 - 2.0x |
| Audio | 2 x 10W (stereo) |
| Noise Level | 28dB Eco |
| Remote Control | IR and wired remote |
| 360 degree and Portrait mode operation | Yes |
| Operating Temperature | Operating: 5 - 40 °C |
| Power Supply | AC input 110- 240V, 50-60 Hz |
| Power Consumption | 380W +/- 15% Max (Bright), 260W +/-15% Max (ECO) |
| High Altitude | Operating temperature at sea level up to 10,000 feet = 104° F (max); Must manually switch to high altitude mode from 5,000 feet and above (using OSD menu) to maintain optimal functionality |

COMPATIBILITY SPECIFICATIONS

| | |
|----------------------------------|--|
| Computer Compatibility | UXGA, SXGA, XGA, SVGA, VGA, WXGA, WUXGA, Mac |
| Video Input Compatibility | SDTV / HDTV |
| 3D Compatibility† | Supports all HDMI 1.4a mandatory 3D formats (frame pack, side-by-side, top-bottom) and up converts frame rate from 60Hz to 120Hz or 24Hz to 144Hz (i.e. 60 or 72 frames per eye). Required 3D glasses are sold separately. Refer to user manual for details. |
| Vertical Scan Rate | 24 ~ 85 Hz |
| Horizontal Scan Rate | 15.375 ~ 91.146 KHz |
| User Controls | LAN, RS-232C, IR individually or over HDBaseT |
| I/O Connection Ports | 2x HDMI, VGA, HDBaseT, mic in (3.5mm), audio in (3.5mm), VGA out (VGA pass-through through to monitor) (monitor out), audio out (3.5mm), 3D sync, 12V trigger, RS-232C (D-sub 9 pin) (PC control), wired remote in (3.5mm phone jack), USB type A (USB power 5V/1.5A), mini USB (for LAN FW upgrade only) (service), IR receiver (on front and top side), RJ45 (LAN) |
| Loop Through (Audio) | NA |


PHYSICAL SPECIFICATIONS

| | |
|-------------------------------|-----------------------|
| Security | Kensington® lock port |
| Weight | 23.6 lb |
| Dimensions (W x H x D) | 15.9" x 6.3" x 15.2" |

Light source life is dependent on brightness mode, display mode, usage, environmental conditions and more. Light source brightness can decrease over time.

Watching 3D projection while wearing 3D glasses for an extended period of time may cause headaches or fatigue. If you experience a headache, fatigue or dizziness, stop viewing the 3D projection and rest.

Portrait orientation must follow the recommended positions. Please consult the user manual for further details.



Warranty

3 Year parts and labor limited warranty on the projector, 5-year or 12,000 hour light source warranty (whichever comes first)

What's in the Box

Power cord, remote control, batteries, VGA cable and quick start guide, user manual CD, warranty card

Optional Accessories

Universal ceiling mount, HDCast Pro, HDBaseT transmitter, 3D glasses

Accessory Part Numbers

Universal ceiling mount: BM-9004U
 HDBaseT transmitter: 4K100TX
 Remote: BR-3075W
 DLP@Link™ 3D glasses: ZD302
 Wireless Mirroring: HDCast PRO-Black

UPC 796435 44 206 4

Optoma.com



Copyright © 2018 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments™. All other trademarks are the property of their respective owners. All specifications subject to change at any time. 05262020